CV6321-000 | TENIO-C6-NT-0-N



TENIO™ Large Fiber Optic Splice Closure, Gel Cable sealing, no pre-installed traus, no flash test valve

- Single-ended, toolless closure for splicing feeder, access and drop cables
- · Features modular building blocks that fastens installation and reduces inventory
- Gel cable sealing technology allows easy adding or removing of a wide size range of cables
- Compatible with most common cable types: e.g. loose tube, central core, ribbon fiber
- Compatible with CommScope's CWDM modules and optical splitter trays

Product Classification

Product Type Single-ended, rectangular fiber closure

Regional Availability EMEA | Latin America

Product Series TENIO

General Specifications

Splicing Type, Supported Single fusion

Splicing Capacity, Single Fusion, maximum 192
Color Black

Network Area Type Distribution | Drop

Package, quantity 1

Packaging Type Box | Carton

Splice Tray Included, quantity 0
Splicing Capacity, Single Splice, 12 fibers, maximum 192

Dimensions

Main Cable Diameter, maximum 16.00 mm

 Height
 230.00 mm | 9.06 in

 Length
 449.00 mm | 17.68 in

 Weight
 1.00 kg | 2.20 lb

 Width
 134.00 mm | 5.28 in

Mechanical Specifications

Cable Sealing TypeCompressed gel

Cable Entry Drop Port StyleGel blockCable Entry Main Port StyleGel blockCable Ports, quantity30Closure Sealing TypeSide latchClosure StyleSingle-ended

page 1 of 2 September 29, 2018



CV6321-000 | TENIO-C6-NT-0-N

Material Type Impact-resistant polymer

Mount Type Wall

Environmental Specifications

Environmental Space Qualification StandardBelow ground | Buried

IEC 61300, 2 m waterhead

Regulatory Compliance/Certifications

AgencyClassificationRoHS 2011/65/EUCompliant