CX1638-000 | FIST-GCOG2-DD6-NN



FIST™ GCOG2 Fiber Optic Splice Closure, Heat Shrink Cable sealing, size DD, no pre-installed fiber trays, 6 ports

Product Classification

Product Type	Single-ended, round fiber closure
Regional Availability	EMEA
Product Series	FIST-GCOG2
Product Brand	FIST™

General Specifications

Splicing Type, Supported	Single fusion
Color	Black
Network Area Type	Distribution
Package, quantity	1
Packaging Type	Box Carton
Splice Tray Included, quantity	0
Splicing Capacity, Single Splice, 2 fibers, maximum	24

Dimensions

Main Cable Diameter, maximum	21.00 mm
Weight	5.50 kg 12.13 lb

Mechanical Specifications

Cable Sealing Type	Compressed gel
Cable Entry Drop Port Style	Round
Cable Entry Main Port Style	Oval
Cable Ports, quantity	7
Closure Sealing Type	Dome-to-base clamp with O-ring
Closure Style	Single-ended
Material Type	Impact-resistant polymer
Mount Type	Pole Strand Wall

Environmental Specifications

Environmental Space	Below ground Buried
Qualification Standard	IEC 61300, 5 m waterhead

page 1 of 2 November 22, 2018

©2018 CommScope, Inc. All rights reserved. All trademarks identified by ® or ™ are registered trademarks, respectively, of CommScope.All specifications are subject to change without notice. See www.commscope.com for the most current information. Revised: October 15, 2018



Regulatory Compliance/Certifications

Agency RoHS 2011/65/EU **Classification** Compliant

> page 2 of 2 November 22, 2018

©2018 CommScope, Inc. All rights reserved. All trademarks identified by ® or ™ are registered trademarks, respectively, of CommScope.All specifications are subject to change without notice. See www.commscope.com for the most current information. Revised: October 15, 2018

