



1. Application / Construction

CH03

Identification	A-DQ(ZN)B2Y nx12 E9 G.652D 3,0 kN		
Application	Outdoor installation		
Cross Section (not to scale)	24/48/72F 	96F 	144F 
Configuration	- Loose tube with up to 12 optical fibers, filled with thixotropic compound - Central strength member made of fibre reinforced plastic (FRP) or coated FRP - Stranding: loose tubes (and dummies), SZ stranded around central strength member - Longitudinal water tightness: dry, water blocking yarns and tape - Peripheral strength member: glass yarns - Outer sheath: black HDPE (Halogen free), with two diametrically opposite orange stripes (width 3~5mm), two red ripcords under the sheath - CPR Fca		
Temperature Range	Storage and transport -30 to +70°C	Installation -10 to +50°C	Operation -30 to +60°C
Standards	IEC 60793-1, IEC 60793-2, IEC 60794-3-10		
ZTT Specification	ZTT 21-116984-1-A		

2. Dimension

Number of fibers		24	48	72	96	144
Loose tubes x fibers		2x12	4x12	6x12	8x12	12x12
Loose tubes / Dummies		4	2	0	0	0
Loose tube Ø	mm	2.3				
Coated FRP/FRP	mm	2.5			3.9 (3.0)	6.9 (3.0)
Outer sheath thickness	mm	1.5				
Outer diameter (±5%)	mm	10.7			12.1	15.1
Weight	kg	94			118	177

Sizes and values without tolerances are nominal values, the sheath thickness is not including the rip cord position.

3. Mechanical Properties

Max. tensile load(Installation)	3000N
Crush resistance / 10 cm	2000N
Bending radius (installation)	20 x cable-Ø
Bending radius (operation)	15 x cable-Ø

See Point 6: Test Methods

4. Marking

Fiber Colors	1 red	2 green	3 yellow	4 blue	5 white	6 violet	7 orange	8 black	9 grey	10 brown	11 pink	12 aqua
Tube Colors	1 red	2 green	3 white	4 white	5 white	6 white	7 white	8 white	9 white	10 white	11 white	12 white

Outer Sheath: black, ink jet or hot foil, marking in 1 meter intervals as follows:

ZTT	OPTICAL CABLE	A-DQ(ZN)B2Y <n>x<m> G.652D	<batch ID>	<meter marking >
------------	----------------------	---	-------------------------	-------------------------------

5. Optical Fiber


Standard	ITU-T G.652D ZTT-ALF®		
Optical	Fibre attenuation .. before cabling .. after cabling	@ 1310 nm ≤0.34 dB/km ≤0.36 dB/km	@ 1550 nm ≤0.20 dB/km ≤0.22 dB/km
	Mode field diameter (MFD)	9.0 ± 0.4 μm	10.4 ± 0.6 μm
	Zero dispersion wavelength	1300~1324 nm	
	Zero dispersion slope	≤0.092 ps/nm ² · km	
	Polarisation mode dispersion (PMD)	≤0.2 ps/√km	
	Cut-off wavelength	≤1260 nm	
	Macro bending loss .. 100 turns Ø50 mm	@1550 nm ≤0.05 dB	@1625 nm ≤0.10 dB
Geometric	Outer diameter	245 ± 10 μm	
	Cladding diameter	125 ± 1.0 μm	
	Core/clad concentricity error	≤0.6 μm	
	Cladding non-circularity	≤1.0 %	
Mechanical	Proof stress	≥0.69 Gpa	

6. Test Methods

Test	Conditions	Acceptance criteria
Tensile strength IEC 60794-1-2 E1	Tensile strength: see Point 3 Sample length: ≥ 50 m, Test duration: 1 min	- Fiber strain: ≤0.33%, Δα reversible - No damage
Crush resistance IEC 60794-1-2 E3	Crush: see Point 3 Test duration: 15 mins, number of tests: 3	- Δα ≤0.05dB after test - No damage
Impact IEC 60794-1-2 E4	Impact energy: 5Nm R = 300 mm, number of places/tests: 3	- Δα ≤0.05dB after test - No damage
Repeated bending IEC 60794-1-2 E6	Bending radius: 20x cable Ø 35 cycles, 100N load	- Δα ≤0.05dB after test - No damage
Torsion IEC 60794-1-2 E7	Sample length: 2 m ± 180°, 10 cycles, 100N	- Δα ≤0.05dB after test - No damage
Bend IEC 60794-1-2 E11A	Bending radius: 15x cable Ø 4 bends, 3 cycles	- Δα ≤0.05dB after test - No damage
Temperature cycling IEC 60794-1-2 F1	-30°C.. +60°C 12 hours at each temperature step, 2 cycles	- Δα≤0.05dB/km - No damage
Water penetration IEC 60794-1-2 F5	Sample length: 3 m Water column height: 1 m Test duration: 24 h	- No water leakage

All optical measurements at 1550 nm

7. Logistics

Cable type	Standard Length (-1% +3%)	4000 m	
A-DQ(ZN)B2Y 24/48/72	Drum type Dimensions (Weight)	Wood 124*50*75 (449 kg)	
A-DQ(ZN)B2Y 96		Wood 144*70*75 (581 kg)	
A-DQ(ZN)B2Y 144		Wood 174*80*75 (867 kg)	

Dimensions including protection. Indicative values, actually delivered drum sizes and weights may deviate. Cable ends sealed with caps

Revision History: A 2021-02-18 Customization Netcom

ZTT International Ltd, No.5,
Zhongtian road, Nantong economic
and technological development zone,
Zip code 226010,
Jiangsu Province, P.R. China

ZTT Maroc SARL d'AU, Zone
Franche d'Exportation de Tanger,
Automotive City
Lot N° 149, Commune Jouamaa,
Province Fahs-Anjra, 90000 Tanger,
Maroc

ZTT Europe GmbH, Falk-Müller-Str.
18
D-97941 Tauberbischofsheim
Tel. +49 9341 8599490
anfrage@zttcable.com

Vertriebspartner Schweiz:**Netcom**
AG, Unterfeldstraße 1-3, CH-8340
Hinwil,
Tel. +41 44 4055050,
info@netcomag.ch