




1. Application / Construction

CH06

Identification	A-DQ(ZN)B2Y nx12 E9 G.652D 6,0 kN		
Application	Outdoor installation		
Cross Section (not to scale)	24/48/72F	96F	144F
			
	<ul style="list-style-type: none"> - Loose tube with up to 12 optical fibers, filled with thixotropic compound - Central strength member made of fibre reinforced plastic (FRP) or coated FRP - Stranding: loose tubes (and dummies), SZ stranded around central strength member - Longitudinal water tightness: dry, water blocking yarns and tape - Peripheral strength member: glass yarns - Outer sheath: black HDPE with two diametrically opposite orange stripes (width 3~5mm), two red ripcords under the sheath 		
Temperature Range	Storage and transport -30 to +70°C	Installation -10 to +50°C	Operation -30 to +60°C
Standards	IEC 60793-1, IEC 60793-2, IEC 60794-3-10		
ZTT Specification	ZTT 21-116894-2-A		

2. Dimension

Number of fibers		24	48	72	96	144
Loose tubes x fibers		2x12	4x12	6x12	8x12	12x12
Loose tubes / Dummies		4	2	0	0	0
Loose tube Ø	mm	2.3				
Coated FRP/FRP	mm	2.5			3.9 (3.0)	6.9 (3.8)
Outer sheath thickness	mm	1.5				
Outer diameter (±5%)	mm	11.4			12.6	15.2
Weight	kg	112			134	188

Sizes and values without tolerances are nominal values, the sheath thickness is not including the rip cord position.

3. Mechanical Properties

Max. tensile load(Installation)	6000 N
Crush resistance / 10 cm	2000 N
Bending radius (installation)	20 x cable-Ø
Bending radius (operation)	15 x cable-Ø

See Point 6: Test Methods

4. Marking

Fiber Colors	1	2	3	4	5	6	7	8	9	10	11	12
	red	green	yellow	blue	white	violet	orange	black	grey	brown	pink	aqua
Tube Colors	1	2	3	4	5	6	7	8	9	10	11	12
	red	green	white	white	white	white	white	white	white	white	white	white

Outer Sheath: black, ink jet or hot foil, marking in 1 meter intervals as follows:

ZTT OPTICAL CABLE A-DQ(ZN)B2Y <n>x12 G.652D 6.0 kN <batch ID> <meter marking >

5. Optical Fiber


Standard	ITU-T G.652D ZTT-ALF®		
Optical	Fibre attenuation .. before cabling .. after cabling	@ 1310 nm ≤0.34 dB/km ≤0.36 dB/km	@ 1550 nm ≤0.20 dB/km ≤0.22 dB/km
	Mode field diameter (MFD)	9.0 ± 0.4 μm	10.4 ± 0.6 μm
	Zero dispersion wavelength	1300~1324 nm	
	Zero dispersion slope	≤0.092 ps/nm ² · km	
	Polarisation mode dispersion (PMD)	≤0.2 ps/√km	
	Cut-off wavelength	≤1260 nm	
	Macro bending loss .. 100 turns Ø50 mm	@1550 nm ≤0.05 dB	@1625 nm ≤0.10 dB
Geometric	Outer diameter	245 ± 10 μm	
	Cladding diameter	125 ± 1.0 μm	
	Core/clad concentricity error	≤0.6 μm	
	Cladding non-circularity	≤1.0 %	
Mechanical	Proof stress	≥0.69 Gpa	

6. Test Methods

Test	Conditions	Acceptance criteria
Tensile strength IEC 60794-1-2 E1	Tensile strength: see Point 3 Sample length: ≥ 50 m, Test duration: 1 min	- Fiber strain: ≤0.33%, Δα reversible - No damage
Crush resistance IEC 60794-1-2 E3	Crush: see Point 3 Test duration: 15 mins, number of tests: 3	- Δα ≤0.05 dB after test - No damage
Impact IEC 60794-1-2 E4	Impact energy: 5Nm R = 300 mm, number of places/tests: 3	- Δα ≤0.05 dB after test - No damage
Repeated bending IEC 60794-1-2 E6	Bending radius: 20x cable Ø 35 cycles, 100N load	- Δα ≤0.05 dB after test - No damage
Torsion IEC 60794-1-2 E7	Sample length: 2 m ± 180°, 10 cycles, 100N	- Δα ≤0.05 dB after test - No damage
Bend IEC 60794-1-2 E11A	Bending radius: 15x cable Ø 4 bends, 3 cycles	- Δα ≤0.05 dB after test - No damage
Temperature cycling IEC 60794-1-2 F1	-30°C.. +60°C 12 hours at each temperature step, 2 cycles	- Δα ≤0.05 dB/km - No damage
Water penetration IEC 60794-1-2 F5	Sample length: 3 m Water column height: 1 m Test duration: 24 h	- No water leakage

All optical measurements at 1550 nm

7. Logistics

Cable type	Standard Length (-1% +3%)	4000 m	
A-DQ(ZN)B2Y 24/48/72	Drum type Dimensions (Weight)	Wood 134*60*75 (544 kg)	
A-DQ(ZN)B2Y 96		Wood 154*70*75 (666 kg)	
A-DQ(ZN)B2Y 144		Wood 174*80*75 (911 kg)	

Dimensions including protection. Indicative values, actually delivered drum sizes and weights may deviate. Cable ends sealed with caps

Revision History: A 2021-02-18 Initial Release

ZTT Europe GmbH, Falk-Müller-Str. 18
D-97941 Tauberbischofsheim, Deutschland
Tel. +49 9341 8599490
anfrage@zttcable.com

ZTT Maroc SARL d'AU, Zone Franche
d'Exportation de Tanger, Automotive City
Lot N° 149, Commune Jouamaa, Province
Fahs-Anjra, 90000 Tanger, Maroc

ZTT International Ltd, No.5, Zhongjian
road, Nantong economic and technological
development zone, Zip code 226010,
Jiangsu Province, P.R. China

Vertriebspartner Schweiz: Netcom AG,
Unterfeldstraße 1-3, CH-8340 Hinwil,
Tel. +41 44 4055050,
info@netcomag.ch